



HYU-740 HYU-740

4MP HYUNDAI NEXTGEN IP BULLET CAMERA WITH 50M INFRARED ILLUMINATION, VANDAL PROOF FOR OUTDOOR USE

KEY FEATURES

- 4MP HYUNDAI NEXTGEN IP bullet camera with 50m infrared illumination, vandal proof for outdoor use
- H.265 + / H.265 / H.264 + / H.264 / MJPEG format
- Triple stream
- CMOS 1/3 "of 4MP
- Digital resolution of 4MP @ 25 fps
- ICR filter
- 0.018 lux
- Motorized optics 2.8 ~ 12 mm with autofocus (104 ° ~ 29 °)
- OSD, AGC, BLC, HLC, WDR real 120dB, 3D-DNR, 1 fixed ROI zone IVS Face detection Two-way audio 1 input / 1 alarm output BNC video output Reset button MicroSD Onvif, ISAPI IP66, IK10 3AXIS 12V CC PoE +



FEATURES

- CMOS sensor 1/3 "4 megapixels
- Up to 4MP (2688x1520) at 25 fps
- 2.8 ~ 12mm motorized optics with autofocus
- H.265 +, H.265, H.264 +, H.264 video compression
- Triple stream
- WDR 120dB, BLC, HLC, 3D-DNR, ROI
- 2 behavior analysis and facial detection
- Infrared lighting up to 50 meters
- MicroSD card slot up to 128GB (card not included)
- IP66 protection degree
- IK10 vandal protection
- Supports PoE +

SPECS

- 2 megapixel 1/3 "CMOS sensor
- Digital resolution: 4MP (2688x1520), 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), etc.
- Compression format H.265 + / H.265 / H.264 + / H.264 / MJPEG
- Stream 1: 4MP, 1080P (25 fps)
- Stream 2: 640x480, 640x360, 320x240 (25 fps)
- Stream 3: 720P, 640x360, 352x288 (25 fps)
- Day / night mode with removable mechanical filter
- Infrared illumination: 50 meters
- Minimum illumination: 0.018 lux F2.0 color (AGC On)
- 2.8 ~ 12 mm motorized optics
- Autofocus control
- Viewing angle: 104 ° ~ 29 ° (H), 55 ° ~ 17 ° (V), 125 ° ~ 34 ° (D)
- OSD menu
- AGC automatic gain control
- Backlight compensation BLC, HLC
- Real WDR 120dB
- 3D digital noise reduction
- 1 fixed ROI zone main stream and secondary stream
- Adjust rotation, brightness, saturation, contrast, sharpness and white balance through client software and web browser
- Intelligent functions: Line crossing detection, intrusion detection
- Facial detection
- BNC video output (only for settings)
- 1 input / 1 audio output
- 1 input / 1 alarm output
- Reset button
- MicroSD / SDHC / SDXC card slot up to 128GB (card not included)
- Network interface: RJ45 (10 / 100M)

- Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug & Play connection with NVR NEXTGEN
- DDNS DEMES compatible
- Power: 12V DC
- Consumption: 1.2A, max. 14.5W
- Supports PoE + 802.3at, class 4
- Operating temperature of 30 ° C ~ + 60 ° C
- Humidity: 95% (no condensation)
- IP66 protection degree
- IK10 vandal protection
- Metal housing
- Dimensions: Ø144.13 x 332.73 (L) mm
- Weight: 1.7 kg
- 3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 90 ° (TILT), 0 ° ~ 360 ° (Rotation)
- Power supply is not included