

IP bullet camera with IR of 30m, for outdoors of 8 MP

- IP bullet camera with IR of 30m, for outdoors of 8 MP
- H.265+/H.265/H.264+/ H.264/MJPEG
- 1/2,5" CMOS, 8MP
- Triple Stream
- Mechanical filter
- 0,01 lux
- 2,8 mm lens (102°)
- OSD, 3D-NR, BLC, HLC, real WDR 120dB, motion detection and privacy mask, ROI
- IVS
- Facial detection
- MicroSD/SDHC/SDXC
- IP67
- 12V DC
- PoE
- Reset button

**Reference / Model****HYU-424 / HYU-424**

IP bullet camera with IR of 30m, for outdoors of 8 MP

Reference / Model

HYU-424 / HYU-424

- 1/2,5" CMOS sensor, 8 MP
- Digital resolution: 8MP (3840x2160), 5MP (3072x1728), 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), VGA (640x480), 360P (640x360), CIF (352x288), QVGA (320x240)
- H.265+/H.265/H.264+/H.264/MJPEG
- Stream 1: 8MP (12,5 fps), 5MP (20 fps), 4MP, 1080P, 720P (25 fps)
- Stream 2: VGA, 360P, QVGA (25 fps)
- Stream 3: 720P, 360P, CIF (25 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 30meters
- Minimum illumination: 0,01 lux (F1.2, AGC On) / 0,028 lux (F2.0, AGC On) / 0 lux IR On
- 2,8 mm lens
- Viewing angle: 102°(H), 53°(V)
- Backlight compensation (BLC, HLC)
- WDRtrue 120dB
- 3D-DNR
- Motion detection and privacy mask, mirror, watermark
- Saturation, brightness, contrast and sharpness adjustable via client software or browser
- 1fixed ROI for stream 1 and independent substream
- Intelligent function: Tripwire detection, intrusion detection
- Facial detection
- MicroSD/SDHC/SDXCup to 128GB (card is not included)
- RJ45 10/100M, auto-adaptive
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
- Compatible with ONVIF (profile S/G), ISAPI
- Up to 6 simultaneous live displays
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Compatible with IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
- Reset button
- Power supply: 12V DC (±25%)
- Consumption: Max 6W
- PoE 802.3af, Class 3
- Working temperature: -30°C ~ +60°C
- RH: <95%, without condensation
- IP67
- Metal case
- Dimensions: Ø70 x 155 mm
- Weight: 410 g
- Power supply is not included