

DM880B

880 Series Push-Button-Activated Manual Call Point In Plastic Housing (Blue)

Allgemein

The DM880 is a BLUE, push-button-activated manual call point. It is supplied in a robust ABS housing and is suitable for indoor surface mounting. The door features a replaceable break glass and allows for an automatic reset when opening and closing the door.

The DB880B is supplied with "Hausalarm" functional marking, and conforms to DIN14655.



Details

- Push-button-activated MCP to DIN14655
- Robust ABS housing
- "Hausalarm" functional indicator
- Automatic reset when opening/closing the door
- VdS approved

DM880B

880 Series Push-Button-Activated Manual Call Point In Plastic Housing (Blue)

Technical specifications

Electrical

Operating voltage	12 to 24 VDC
Current consumption	7 mA

Physical

Physical dimensions	125 x 125 x 36 mm (W x H x D)
Net weight	225 g
Colour	Blue (RAL 5005)
Door opening angle	>180°
Material	PA6 + 30%GF

Environmental

Operating temperature	-40 to +80°C
Environment	Indoor
IP rating	IP42

Compatible products

Category	Reference	Description
Detection device	DM966	Replacement clear windows for push-button activated manual call points



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 August 2024 - 14:31