

# AS964I

## Apollo XP95 Loop Powered Open-Area Sounder (Red) With Isolator (55000-001)

### General

---

The AS964I is a 950 series, intelligent loop powered open-area sounder in RED with a built in isolator. It is designed for use in indoor and outdoor open area applications. It supports 3 tones with two volume settings.

A locking mechanism is available to prevent unauthorized removal of the AS964I from its base.

### Isolation and Maintenance

---

The AS964I sounder is supplied with an isolating base. A yellow LED on the base is illuminated if a loop short circuit is detected. All fault and abnormal conditions such as sounder failures are reported back to the panel for easy faultfinding.

### Sounder Tone Support

---

That AS964I supports the following tones:

- Standard
- Slow Whoop (NEN2575)
- DIN (33404pt3)

Two volume settings are available in each tone variant.



### Details

---

- Self-test fault monitoring
- Multiple tones
- Alarm synchronisation
- Loop powered
- Including loop isolator

# AS964I

## Apollo XP95 Loop Powered Open-Area Sounder (Red) With Isolator (55000-001)

### Technical specifications

---

#### Electrical

---

Operating voltage	17 to 28 VDC
Current consumption	Quiescent: <333 $\mu$ A @ 24 VDC Switch on surge (< 1 s): <1.2 mA @ 24 VDC Alarm (Sounder only): 5 mA @ 24 VDC

---

#### Sounder

---

Output level	100 dB(A) @ 90° ( $\pm$ 3dB(A))
Frequency	Tone dependant

---

#### Environmental

---

Environment	Indoor
IP rating	IP65

---

#### Regulatory

---

Certification	EN54-17, EN54-3
---------------	-----------------

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 13 August 2024 - 7:52