


ACT407E

(25 PACK) Mifare Classic card S50 with 7-byte UID serial number (CSN)

Product overview

These Mifare Classic1k cards are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other Carrier Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



Details

- Read only for CSN (7-byte)
- Read / Write function for card sectors
- Packed by 25

ACT407E

(25 PACK) Mifare Classic card S50 with 7-byte UID serial number (CSN)

Technical specifications

System

Reading distance	0 to 10 cm
Memory size	1 kB
No. of Mifare bytes CSN	7 Bytes (S50)
Supported readers	ACI406/407 Mifare Readers, ATS1160/1161 Mifare Readers

Technology

Credential type	Proximity
Credential operating frequency	13.56 MHz
Supported technology	MIFARE Classic (CSN) 13.56 MHz

Ordering information

Cards/tags in package	25
-----------------------	----

Physical

Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	86 x 54 mm
Colour	White



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:32