

**IP WiFi bullet camera with IR of 30m, for outdoors, 4 MP**

- IP WiFi bullet camera with IR of 30m, for outdoors, 4 MP
- H.265+/H.265/H.264+/H.264/MJPEG
- 1/3" CMOS, 4MP
- Dual stream
- Mechanical filter
- 0,028 lux
- 2,8 mm lens (100°)
- OSD, AGC, 3D-DNR, BLC, digital WDR, privacy mask, ROI
- Microphone incorporated
- MicroSD/SDHC/SDXC
- IP66
- 3AXIS
- 12V DC.



Reference / Model	HYU-663 / HYU-663
1/3" CMOS sensor, 4 MP	
2560x1440 at 20 fps	
2,8 mm lens	
WiFi connectivity	
H.265+/H.265/H.264+/H.264	
3D DNR	
Microphone incorporated (mono)	
IP66	
Specs	
1/3" CMOS sensor, 4 MP	
Digital resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), etc.	
H.265+/H.265/H.264+/H.264/MJPEG	
Stream 1: 4MP (20 fps), 3MP, 1080P, 720P (25 fps)	

## IP WiFi bullet camera with IR of 30m, for outdoors, 4 MP

Reference / Model	HYU-663 / HYU-663
Stream 2: 640x480, 640x360,320x240 (25 fps)	
Day/night mode with removable mechanical filter	
IR illumination: 30meters	
Minimum illumination: 0,028 lux F2.0 color / 0 lux IR On	
2,8 mm lens	
Viewing angle: 100°H, 55°V and 117°D	
Automatic Gain Control	
Backlight compensation	
Digital WDR	
3D DNR	
Privacy mask, mirror, watermark	
1 ROI on stream1	
Adjustment: brightness, saturation, contrast and sharpness via client software and web browser	
Incorporates microphone with monaural sound	
Reset button	
Card slot MicroSD/SDHC/SDXC up to 128GB (card is not included)	
Network interface: RJ45 (10/100M) auto-adaptive	
Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, UDP, Bonjour	
WiFi 802.11b/g/n at 2,4GHz with WEP, WPA/WPA2, WPA-PSK/WPA-PSK2and WPS	
WiFi range up to 50 meters in open field without obstacles	
Compatible with ONVIF (Profile S / G), ISAPI	
Plug & Play connection with NVR NEXTGEN	
Compatible with DDNS DEMES	
Degree of protection IP66	
Power: 12V DC, max 6W	

**IP WiFi bullet camera with IR of 30m, for outdoors, 4 MP**

Reference / Model	HYU-663 / HYU-663
Operating temperature of -30 ° C ~ + 60 ° C	
Humidity: <95%, without condensation	
Plastic and metal housing	
Dimensions: 69.7 (W) x 67.9 (H) x 171.4 (L) mm	
Weight: 372 g	
3AXIS: 0 ° ~ 360 ° (PAN), 0 ° ~ 90 ° (TILT), 0 ° ~ 360 ° (Rotation)	
Power supply is not included	